

SPECIFICATION SHEET

HATCHGUARD ROOF RAILING SYSTEM

DID YOU KNOW...

It is required by law that each employee on a walking /working surface with an unprotected surface opening must be protected by the use of guardrail, safety net or personal fall arrest systems.

HATCHGUARD

A versatile, economic and modular fall protection system designed to protect employees/contractors entering, exiting or working around roof hatches.

Our system requires no penetration of the roof surface. Our counterweighted system utilizes stackable cast steel base plates create a freestanding, self reinforcing system that meets all lateral force loading requirements. Consists of aluminum pipe, magnesium alloy fittings, spring loaded safety gate and galvanized steel base plates.

Easy to use, easy to install, saves lives!

MEETS AND EXCEEDS ALL MAJOR NORTH AMERICAN SAFETY STANDARDS

OHSA NBC CSA CE
OBC OSHA BS EN


MOL ANSI WORKSAFEBC





HATCHGUARD ROOF RAILING SYSTEM: INCLUDING POSTS, RAILS, BASES, AND FITTINGS.

Freestanding counterweighted guardrail system with 42 inches minimum height provides a barrier for workers on the roof and must be designed to withstand OBC loading criteria.





WHY ROOFGUARD?

- Systems are customizable and can be configured to best suit the customer's needs
- User friendly and ergonomic
- Ships on compact skids (low shipping costs)
- Low cost & easy installation

REQUEST A FOLLOW-UP

Email: info@liftsafegroup.com

Call: 1-800-977-2005



