



AIRCRAFT MAINTENANCE AND ENGINE ACCESS STANDS

AVAILABLE ACCESSORIES

- Air powered pump
- Fork pockets
- Fold away tow bar
- Leveling jacks
- Platform adaptors
- Straight extension
- Utilities package
- 777X pylon extension



TECHNICAL SPECIFICATIONS

MODEL NO.	DF071554-06	DF071554-07-08	DF071554-07-10	DF071554-07-12
DESIGNED FOR	Engine Access, Engines (Under "C" Duct), Outboard Engines, Pylons, Wing Refuel Panel, Bulk Cargo, Aft Pressure Bulkhead Access Panel, APU Servicing, Wing Tip Nav Lights, Flap Canoes / Fairings, Wing Landing Lights, Passenger Windows, Wing Access, Main Entry Door Sills, Windshield Inspections, Pitot Probe Tube Inspections/Replacements, AOA/True Airspeed Probes Inspections / Replacements, Static Port Inspections/Replacements & Trailing Edge Actuator Inspections/Replacements			
AIRCRAFT TYPE	A340, A380, A400, B747, DOUGLAS DC-10/MD-10/ MD-11	A300, A310, A318, A319, A320, A321, A330, B717, B727, B747, B757, B767, B787, Bombardier CRJ, E-170, E-190, McDonnell Douglas DC-9 Super 80/ MD-80	A300, A330, A340, A350, A380, B757, B777, Lockheed L-1011	B777X & 777 Legacy
MOVEMENT	2 Persons	1 Person	1 Person	1 Person
TOWING SPEED	6 MPH / 10 KPH	6 MPH / 10 KPH	6 MPH / 10 KPH	6 MPH / 10 KPH
FOOTPRINT	89 7/8" x 161 3/4" / 228.2cm x 411.8cm	87 3/4" x 122 7/8" / 223.4cm x 312.1cm	87 3/4" x 122 7/8" / 223.9cm x 312.1cm	87 3/4" x 122 7/8" / 223.9cm x 312.1cm
SHIPPING (DIMS)	89 1/4" x 64 1/2" x 163 3/16" x 2,400 lbs / 227.8cm x 163.8cm x 414.4cm x 1,088.6kg	88" x 50" x 123" x 1,050 lbs / 223.5cm x 127cm x 312.4cm x 476.2kg	88" x 52" x 128" x 1,100 lbs / 223.5cm x 132cm x 325.1cm x 498.9kg	88" x 52" x 108 3/4" x 1,150 lbs / 223.5cm x 132cm x 274.9cm x 521.6kg
HEIGHT	Low: 126 1/2" / 321.3cm High: 239 1/4" / 607.6cm	Low: 129 7/16" / 328.7cm High: 183 3/8" / 465.7cm	Low: 152 3/8" / 387cm High: 207" / 525.7cm	Low: 187 1/4" / 475.6cm High: 224 1/2" / 570.2cm
WEIGHT CAPACITY	330 lbs / 150 kg	330 lbs / 150 kg	330 lbs / 150 kg	330 lbs / 150 kg
CERTIFICATIONS	ANSI-ASC A14.7, BS EN 131.7, CE, DIN EN 12312-8 & EN 1915-1			
ANGLES	73-83 Degrees	73-83 Degrees	73-83 Degrees	52-75 Degrees
MATERIAL	Ladder: Aluminum Frame: Steel	Ladder: Aluminum Frame: Aluminum	Ladder: Aluminum Frame: Aluminum	Ladder: Aluminum Frame: Aluminum
FINISH	Powder Coated Finish	Powder Coated Finish	Powder Coated Finish	Powder Coated Finish
NUMBER OF USERS	1 User	1 User	1 User	1 User
CASTOR DETAILS	8" / 20.3cm Split Castor with Brake and Swivel Lock	8" / 20.3cm Split Castor with Brake and Swivel Lock	8" / 20.3cm Split Castor with Brake and Swivel Lock	8" / 20.3cm Split Castor with Brake and Swivel Lock
CONTROLS	Hydraulic Foot Pump	Hydraulic Foot Pump	Hydraulic Foot Pump	Hydraulic Foot Pump
FULLY EXTENDED	Ladder: 128 Strokes Tilt: 43 Strokes Scissors: 86 Strokes	Ladder: 57 Strokes Tilt: 23 Strokes	Ladder: 57 Strokes Tilt: 23 Strokes	Ladder: 57 Strokes Tilt: 23 Strokes
FALL RESTRAINT ANCHOR POINTS	Equipped	Equipped	Equipped	Equipped
PADDING MATERIAL	Equipped	Equipped	Equipped	Equipped