



TIRE TRAILERS

DESCRIPTION

The Tire Trailer was designed to provide safe transportation of aircraft wheel assemblies, brakes and required tooling, while maintaining the storage requirements of regulatory bodies (EASA, TC, FAA).

Liftsafe Fall Protection has designed numerous sizes of standard and custom Tire Trailers based on operational needs. The low-profile design and lightweight swing gates ensure safety of maintenance staff during use. Foam filled tires are available upon request.

Our Professional Engineers will work with you to determine what size Aviation Tire Trailer works best within your operation.

WHAT OUR CUSTOMERS ARE SAYING

"We find that Liftsafe Fall Protection is more than willing to work with us in creating safe, economical and multi-purpose designed equipment, tailored to our needs."



NATO N/CAGE CODE: L03Y4



member of

NBAA



PRODUCT FEATURES

- Low profile design
- Lightweight swing gates
- Safe transportation of aircraft wheel assemblies and tools
- Enclosed versions available
- Steel or aluminum construction
- Maintains the storage requirements of regulatory bodies (EASA, TC, FAA)

BENEFITS

- Low profile design and lightweight swing gates ensure safety of maintenance staff during use
- Foam-filled tires are available upon request
- Provides safe transportation of aircraft wheel assemblies, brakes and required tooling
- Can be configured to carry associated tire change jacks and tools
- Optional Nitrogen
- 2 year limited warranty on components
- 10 year limited warranty on structure



TIRE TRAILERS

AVAILABLE ACCESSORIES

- Brake lifting hoist
- Foam filled tires
- Solid tires
- Full-hard or soft cover
- Nitrogen bottle holders
- Surge braking system
- Tool boxes



TECHNICAL SPECIFICATIONS

DF081002

DESIGNED FOR	Transports Wheel & Break Assemblies	
AIRCRAFT TYPE	All Aircraft Types	
MOVEMENT	Pintle, Towed	
TOWING SPEED	50 KPH / 31 MPH	
SHIPPING (DIMS)	Based Upon Customer Requirements	
DECK HEIGHT	5' 3/4" / 12.7cm Or As Required	
WIDTH	116" / 294.6 Or As Required	
WEIGHT CAPACITY	1134kg / 2,500lbs Or As Required	
CONFIGURATION	Based Upon Customer Requirements	
MATERIAL	Structure: Steel or Aluminum	Ramps: Steel or Aluminum
FINISH	Based Upon Customer Requirements	
WHEELS	15" / 38.1cm or 16" / 40.6cm Wheels Based on Customer Requirements	
PADDING MATERIAL	As Required	