



SPECIFICATION SHEET

RACKGUARD NETTING SYSTEMS

FLUSHMOUNT

Netting sits flush to the racking system. Ideal where there is no pallet overhang or product is loaded by hand.

STANDARD OFFSET

Netting is installed standard distances away from the face of the racking, allowing for pallet/product overhang.

FLUE SPACE

Netting is installed in the flue space between racking systems to reduce product loss and keep products from getting mixed up.

HORIZONTAL

Netting installed with our custom mounting brackets inside the rack horizontally to prevent product falling risks from an upper level.

RACKGUARD NETTING SYSTEMS

An “engineered” system consisting of custom-fitted netting panels, rigging hardware, and brackets.

SPECIFICATION

DETAILS

Product Name	RackGuard Industrial Safety Netting
Manufacturer	Liftsafe Fall Protection Inc.
Safety Standards Compliance	OSHA, MOL, ANSI, WorkSafeBC, OBC, NBC, CSA, BS EN, CE Certification
Netting Panel	2500 lbs net - 2” square, industrial safety netting 3000 lbs net - 2” square, industrial safety netting 6000 lbs net - 2-1/2” square, fall arrest netting
Netting Colour	Black, yellow, custom colours are available for large orders
Netting Material	2500 lbs net - nylon 3000 lbs net - nylon 6000 lbs net - HTPP
Netting Cable	1/4” aircraft cable (for up to 3000 lbs pallets) 3/8” (for 3500 - 5000 lbs pallet loads)
Netting Design	Knotless netting, sewn rope border, UV protection
Rigging Components	Galvanized cable, wire rope clips, thimbles, turnbuckles, eyebolts, safety snap hooks
Offset Brackets	Available offset brackets: 2”, 3”, 4”, 6”, 9”, 10”, 12” & custom sizes, flushmount options available
Extension Bracket	Available from 1’ up to 6’ in height



Liftsafe Fall Protection Inc.
A Division of Liftsafe Group of Companies
409 Harmony Rd, Ayr, ON N0B 1E0
P: (519) 896-2430 | TF: (800) 977-2005 | F: (519) 896-2085
E: info@liftsafegroup.com | W: www.liftsafegroup.com

