

FIXED LADDERS ROOFCLIMB SERIES

The Fixed Ladders RoofClimb Series provides safe and efficient access to rooftops and elevated surfaces. Designed with modularity in mind, these ladders are shipped as easy-to-assemble kits and bolted together on-site, eliminating the need for welding. This innovative design ensures quick installation, lower shipping costs, and the flexibility to make adjustments as needed. Ideal for a variety of applications, RoofClimb ladders are built to meet safety standards while offering unmatched convenience.

FEATURES

Modular Design: Shipped as kits and bolted together on-site for easy assembly.

No Welding Required: Simplifies installation and allows for quick adjustments.

Cost-Effective: Lower shipping costs due to compact, modular packaging.

Flexible: Can be reconfigured or adjusted to fit various rooftop layouts.

Durable: Built with high-quality materials to ensure long-lasting performance.

FIXED LADDERS ROOFCLIMB SERIES

Safe and efficient access to rooftops and elevated surfaces.

SPECIFICATIONS

Material

Ladder Rail & Posts	Ø1-1/2" (Ø1.9 OD) Schedule 40 Aluminum Pipe 6061-T6 – 0.97lbs/ft
Ladder Components	High-grade 5000 & 6000 structural aluminum
Hardware	All stainless steel
Fittings	Ø1-1/2" (Ø1.9 OD) Aluminum Magnesium
End Caps	Plastic inserts
Finish	Mill finished (standard); powder coating available at an upcharge
Dimensions	
Rail Spacing	24" (610mm)
Overall Width	27-3/4" (705mm)
Ladder Rail Length	10 ft lengths
Ladder Rung	1-1/4" SQ. 6061-T6, machined serrated top surface
Rung Spacing	12in (305mm)
Rail Extension	42" (1067mm) beyond landing surface
Clearance Behind Ladder	7in (178mm) minimum (vertical position)
Weight	
Ladder Section (10 ft)	90 lbs (includes rungs, fittings, & hardware)
Cage Section (10 ft)	60 lbs (includes hardware)
Compliance	Meets/exceeds all major North American safety standards: OHSA, NBC, CSA, CE Certification, OBC, OSHA, BS EN, MOL, ANSI, and WorkSafeBC
Warranty	5 years

