





CAP (TON)




SPAN (FT)



WHEEL BASE
(FT)



WHEEL LOAD
(LBS)



BEAM WIDTH
(IN)



STANDARD
HEADROOM (IN)



SHIP WT
(LBS)

SINGLE GIRDER DUAL DRIVE TOP RUNNING BRIDGE CRANE

[1 TON TO 50 TON MODELS AVAILABLE]

We manufacture Overhead Cranes and Bridge Cranes that offer exceptional reliability and dependability at competitive prices. With over a 100 standard Single Girder Top Running Overhead Crane models available, we are the leading manufacturer and installer of Overhead Cranes in Canada.

When selecting an Overhead Crane it is important to first understand the needs of your system and select a product that will provide a reliable solution in your particular environment, that works with your facilities structural capabilities. Single Girder Top Running Overhead Cranes are designed to travel on top of a runway system that can be either supported by engineered columns or existing building columns. Our collaborative approach ensures that the Overhead Crane System you select exceeds your expectations for not only quality but reliability. We assess your facilities capabilities, evaluate the needs of the system, determine weight and span requirements, and recommend systems that are tailored to your specific needs.

Liftsafe Engineering and Service Group Inc., partners with industry leading suppliers to offer exceptional parts and components when designing and manufacturing Overhead Crane Systems. What that means is we provide our Customers with only the most innovative and technologically advanced components when designing and manufacturing a Crane System.

Contact an expert Overhead Crane Specialist for a free no-obligation assessment of your facility. Let us show you why our over 25 years of Overhead and Bridge Crane Manufacturing experience sets us apart from the competition and how we can increase productivity and safety at your facility!



MODEL (PART ID)	SPAN (FT)	WHEEL BASE (FT)	WHEEL LOAD (LBS)	BEAM WIDTH (IN)	STANDARD HEADROOM (IN)	SHIP WT (LBS)
ITRX-TRC-DDSG-2000-16	16	4.50	1,630	5.25	18.25	1,050
ITRX-TRC-DDSG-2000-20	20	4.50	1,740	5.77	20.50	1,350
ITRX-TRC-DDSG-2000-24	24	4.50	1,800	5.77	20.50	1,490
ITRX-TRC-DDSG-2000-28	28	4.50	1,880	6.52	22.50	1,760
ITRX-TRC-DDSG-2000-32	32	4.50	1,980	6.56	22.50	2,100
ITRX-TRC-DDSG-2000-36	36	4.50	2,110	7.99	23.75	2,585
ITRX-TRC-DDSG-2000-40	40	6.00	2,225	8.03	24.00	3,015
ITRX-TRC-DDSG-2000-44	44	6.00	2,350	8.06	24.00	3,485
ITRX-TRC-DDSG-2000-48	48	6.00	2,640	7.64	28.50	4,640
ITRX-TRC-DDSG-2000-52	52	7.50	2,890	8.35	31.50	5,620
ITRX-TRC-DDSG-2000-56	56	7.50	3,140	8.42	31.75	6,590
ITRX-TRC-DDSG-2000-60	60	7.50	3,265	9.06	34.50	7,090



ITRX-TRC-DDSG-4000-16	16	4.50	2,625	5.77	20.50	1,205
ITRX-TRC-DDSG-4000-20	20	4.50	2,745	6.52	22.50	1,440
ITRX-TRC-DDSG-4000-24	24	4.50	2,865	6.56	22.50	1,740
ITRX-TRC-DDSG-4000-28	28	4.50	3,000	7.99	23.75	2,160
ITRX-TRC-DDSG-4000-32	32	4.50	3,120	8.03	24.00	2,550
ITRX-TRC-DDSG-4000-36	36	4.50	3,245	8.06	24.00	2,980
ITRX-TRC-DDSG-4000-40	40	6.00	3,510	7.64	28.50	3,995
ITRX-TRC-DDSG-4000-44	44	6.00	3,740	8.35	31.50	4,880
ITRX-TRC-DDSG-4000-48	48	6.00	3,975	8.42	31.75	5,770
ITRX-TRC-DDSG-4000-52	52	7.50	4,240	12.75	34.25	6,800
ITRX-TRC-DDSG-4000-56	56	7.50	4,360	12.75	34.25	7,255
ITRX-TRC-DDSG-4000-60	60	7.50	4,480	12.75	34.25	7,710



ITRX-TRC-DDSG-6000-16	16	4.50	3,870	6.56	22.50	2,030
ITRX-TRC-DDSG-6000-20	20	4.50	4,020	6.77	24.25	2,280
ITRX-TRC-DDSG-6000-24	24	4.50	4,160	7.99	23.75	2,600
ITRX-TRC-DDSG-6000-28	28	4.50	4,290	8.03	24.00	2,970
ITRX-TRC-DDSG-6000-32	32	4.50	4,425	8.06	24.00	3,380
ITRX-TRC-DDSG-6000-36	36	4.50	4,685	7.64	28.50	4,320
ITRX-TRC-DDSG-6000-40	40	6.00	4,915	8.35	31.50	5,155
ITRX-TRC-DDSG-6000-44	44	6.00	5,140	8.42	31.75	6,005
ITRX-TRC-DDSG-6000-48	48	6.00	5,400	12.75	34.25	6,990
ITRX-TRC-DDSG-6000-52	52	7.50	5,525	12.75	34.25	7,450
ITRX-TRC-DDSG-6000-56	56	7.50	5,650	12.75	34.25	7,905
ITRX-TRC-DDSG-6000-60	60	7.50	5,975	12.80	34.50	9,175



CAP (TON)




SPAN (FT)



WHEEL BASE (FT)



WHEEL LOAD (LBS)



BEAM WIDTH (IN)



STANDARD HEADROOM (IN)



SHIP WT (LBS)

SINGLE GIRDER DUAL DRIVE TOP RUNNING BRIDGE CRANE

[1 TON TO 50 TON MODELS AVAILABLE]

We manufacture Overhead Cranes and Bridge Cranes that offer exceptional reliability and dependability at competitive prices. With over a 100 standard Single Girder Top Running Overhead Crane models available, we are the leading manufacturer and installer of Overhead Cranes in Canada.

When selecting an Overhead Crane it is important to first understand the needs of your system and select a product that will provide a reliable solution in your particular environment, that works with your facilities structural capabilities. Single Girder Top Running Overhead Cranes are designed to travel on top of a runway system that can be either supported by engineered columns or existing building columns. Our collaborative approach ensures that the Overhead Crane System you select exceeds your expectations for not only quality but reliability. We assess your facilities capabilities, evaluate the needs of the system, determine weight and span requirements, and recommend systems that are tailored to your specific needs.

Liftsafe Engineering and Service Group Inc., partners with industry leading suppliers to offer exceptional parts and components when designing and manufacturing Overhead Crane Systems. What that means is we provide our Customers with only the most innovative and technologically advanced components when designing and manufacturing a Crane System.

Contact an expert Overhead Crane Specialist for a free no-obligation assessment of your facility. Let us show you why our over 25 years of Overhead and Bridge Crane Manufacturing experience sets us apart from the competition and how we can increase productivity and safety at your facility!



5

MODEL (PART ID)	SPAN (FT)	WHEEL BASE (FT)	WHEEL LOAD (LBS)	BEAM WIDTH (IN)	STANDARD HEADROOM (IN)	SHIP WT (LBS)
ITRX-TRC-DDSG-10000-16	16	4.50	5,670	7.03	26.25	2,200
ITRX-TRC-DDSG-10000-20	20	4.50	5,890	7.07	26.50	2,555
ITRX-TRC-DDSG-10000-24	24	4.50	6,085	7.12	26.50	2,985
ITRX-TRC-DDSG-10000-28	28	4.50	6,325	7.64	28.50	3,675
ITRX-TRC-DDSG-10000-32	32	4.50	6,560	8.35	31.50	4,415
ITRX-TRC-DDSG-10000-36	36	4.50	6,790	8.42	31.75	5,185
ITRX-TRC-DDSG-10000-40	40	6.00	7,045	12.75	34.25	6,080
ITRX-TRC-DDSG-10000-44	44	6.00	7,180	12.75	34.25	6,535
ITRX-TRC-DDSG-10000-48	48	6.00	7,315	12.75	34.25	6,990
ITRX-TRC-DDSG-10000-52	52	7.50	7,625	12.80	34.50	8,160
ITRX-TRC-DDSG-10000-56	56	7.50	7,975	12.85	34.50	9,490
ITRX-TRC-DDSG-10000-60	60	7.50	8,370	12.90	34.75	11,020



7.5

ITRX-TRC-DDSG-15000-16	16	4.50	8,110	7.12	28.50	2,700
ITRX-TRC-DDSG-15000-20	20	4.50	8,420	7.59	30.50	3,145
ITRX-TRC-DDSG-15000-24	24	4.50	8,670	7.64	30.50	3,605
ITRX-TRC-DDSG-15000-28	28	4.50	8,940	8.35	33.50	4,295
ITRX-TRC-DDSG-15000-32	32	4.50	9,205	9.06	36.50	5,070
ITRX-TRC-DDSG-15000-36	36	4.50	9,460	12.75	36.25	5,870
ITRX-TRC-DDSG-15000-40	40	6.00	9,620	12.75	36.25	6,330
ITRX-TRC-DDSG-15000-44	44	6.00	9,920	12.80	36.50	7,390
ITRX-TRC-DDSG-15000-48	48	6.00	10,255	12.85	36.50	8,610
ITRX-TRC-DDSG-15000-52	52	7.50	10,635	12.90	36.75	10,015
ITRX-TRC-DDSG-15000-56	56	7.50	11,050	12.95	37.00	11,585
ITRX-TRC-DDSG-15000-60	60	7.50	11,485	14.09	40.00	13,260



10

ITRX-TRC-DDSG-20000-16	16	4.50	10,810	8.35	33.50	3,185
ITRX-TRC-DDSG-20000-20	20	4.50	11,180	8.35	33.50	3,555
ITRX-TRC-DDSG-20000-24	24	4.50	11,525	8.42	33.75	4,200
ITRX-TRC-DDSG-20000-28	28	4.50	11,765	9.06	36.50	4,655
ITRX-TRC-DDSG-20000-32	32	4.50	12,170	12.80	36.50	5,870
ITRX-TRC-DDSG-20000-36	36	4.50	12,510	12.85	36.50	6,920
ITRX-TRC-DDSG-20000-40	40	6.00	12,710	12.85	36.50	7,485
ITRX-TRC-DDSG-20000-44	44	6.00	13,080	12.90	36.75	8,765
ITRX-TRC-DDSG-20000-48	48	6.00	13,485	12.95	37.00	10,210
ITRX-TRC-DDSG-20000-52	52	7.50	13,905	14.09	40.00	11,755
ITRX-TRC-DDSG-20000-56	56	7.50	14,315	15.04	42.75	13,270
ITRX-TRC-DDSG-20000-60	60	7.50	14,700	15.74	45.75	14,720



CAP (TON)




SPAN (FT)



WHEEL BASE
(FT)



WHEEL LOAD
(LBS)



BEAM WIDTH
(IN)



STANDARD
HEADROOM (IN)



SHIP WT
(LBS)

SINGLE GIRDER DUAL DRIVE TOP RUNNING BRIDGE CRANE

(1 TON TO 50s TON MODELS AVAILABLE)

We manufacture Overhead Cranes and Bridge Cranes that offer exceptional reliability and dependability at competitive prices. With over a 100 standard Single Girder Top Running Overhead Crane models available, we are the leading manufacturer and installer of Overhead Cranes in Canada.

When selecting an Overhead Crane it is important to first understand the needs of your system and select a product that will provide a reliable solution in your particular environment, that works with your facilities structural capabilities. Single Girder Top Running Overhead Cranes are designed to travel on top of a runway system that can be either supported by engineered columns or existing building columns. Our collaborative approach ensures that the Overhead Crane System you select exceeds your expectations for not only quality but reliability. We assess your facilities capabilities, evaluate the needs of the system, determine weight and span requirements, and recommend systems that are tailored to your specific needs.

Liftsafe Engineering and Service Group Inc., partners with industry leading suppliers to offer exceptional parts and components when designing and manufacturing Overhead Crane Systems. What that means is we provide our Customers with only the most innovative and technologically advanced components when designing and manufacturing a Crane System.

Contact an expert Overhead Crane Specialist for a free no-obligation assessment of your facility. Let us show you why our over 25 years of Overhead and Bridge Crane Manufacturing experience sets us apart from the competition and how we can increase productivity and safety at your facility!



MODEL (PART ID)	SPAN (FT)	WHEEL BASE (FT)	WHEEL LOAD (LBS)	BEAM WIDTH (IN)	STANDARD HEADROOM (IN)	SHIP WT (LBS)
ITRX-TRC-DDSG-30000-16	16	4.50	16,500	12.85	38.50	5,400
ITRX-TRC-DDSG-30000-20	20	4.50	17,055	12.85	38.50	5,965
ITRX-TRC-DDSG-30000-24	24	4.50	17,575	12.85	38.75	6,940
ITRX-TRC-DDSG-30000-28	28	4.50	17,930	12.90	38.75	7,565
ITRX-TRC-DDSG-30000-32	32	4.50	18,230	12.90	38.75	8,190
ITRX-TRC-DDSG-30000-36	36	4.50	18,660	12.90	39.00	9,440
ITRX-TRC-DDSG-30000-40	40	6.00	18,920	12.95	39.00	10,130
ITRX-TRC-DDSG-30000-44	44	6.00	19,355	14.09	42.00	11,555
ITRX-TRC-DDSG-30000-48	48	6.00	19,770	15.04	44.75	12,965
ITRX-TRC-DDSG-30000-52	52	7.50	20,160	15.74	47.75	14,330
ITRX-TRC-DDSG-30000-56	56	7.50	21,130	15.75	53.50	18,025
ITRX-TRC-DDSG-30000-60	60	7.50	21,430	15.75	53.50	19,060



CONSULT FACTORY FOR SPECIFICATIONS



LIFTSAFE

liftsafeinspections.com